

Stainless Steel Wire Rope Clips (Bulldog Grips)

Product Features

Manufactured in accordance with American Federal Specification & DIN 741
 Free from sharp edges - good smooth finish all round
 High corrosion resistance

Quality Features

High quality finish and excellent polish


Typical Applications

Wire Rope Slings
 Chemical installations - Chlorine plants etc
 General lifting in off-shore applications
 General lifting purposes


Correct Use

There is a lot of wrong information in the field regarding the right way to install wire rope slips, the most common being that the clips should be staggered during installation. Since more friction equals more efficiency, it stands to reason that the saddle, because of its larger surface area, must be installed on the live side of the rope. Having the saddle on the live side also greatly reduces the possibility of rope damage.

Please visit our website www.liftingshackles.com for more details.




Wire Rope Clip



DIN 741



Wire rope Clip Top Down American Fed Spec



STAINLESS STEEL GRADE 316 TO AMERICAN FEDERAL SPECIFICATION

DIMENSIONS & WLL									PRODUCT NUMBER
Wire Dia	A	B1	B2	D	H1	H2	L	Weight	
2.0	9.0	4.0	13.0	M3	18	11.0	14.0	0.00080	CLIP-02
3.0	12.0	5.0	16.0	M4	25	12.0	17.0	0.01500	CLIP-03
4.0	13.0	6.0	18.0	M4	25	14.0	19.0	0.02900	CLIP-04
5.0	15.0	7.0	20.0	M5	29	15.0	24.0	0.03100	CLIP-05
6.0	18.0	8.0	21.0	M6	31	17.0	27.0	0.04000	CLIP-06
8.0	23.0	10.0	27.0	M8	41	21.0	34.0	0.07700	CLIP-08
10.0	28.0	12.0	34.0	M10	52	25.0	45.0	0.17000	CLIP-10
12.0	35.0	14.0	38.0	M12	61	28.0	51.0	0.26500	CLIP-12
14.0	42.0	15.0	43.0	M12	68	32.0	52.0	0.31000	CLIP-14
16.0	42.0	18.0	47.0	M14	76	36.0	60.0	0.50000	CLIP-16
19.0	50.0	20.0	51.0	M14	79	40.0	62.0	0.58000	CLIP-19
22.0	60.0	26.0	61.0	M16	98	46.0	72.0	0.80000	CLIP-22
25.0	62.0	29.0	61.0	M16	110	49.0	76.0	1.08000	CLIP-25

LIGHTWEIGHT VERSION - STAINLESS STEEL GRADE 316 TO DIN 741

DIMENSIONS & WLL								PRODUCT NUMBER
Wire Dia	A	B	D1	H1	H2	T	Weight	
2.0	17.0	11.0	M3	17.5	10.00	10.0	0.00070	CLIPL-02
3.0	18.0	12.0	M3	21.0	11.00	10.0	0.01200	CLIPL-03
4.0	21.0	14.0	M4	23.0	13.00	11.0	0.01400	CLIPL-04
5.0	25.0	15.0	M5	28.0	15.00	12.0	0.01500	CLIPL-05
6.0	28.0	17.0	M6	32.0	17.00	16.0	0.02100	CLIPL-06
8.0	31.0	21.0	M6	36.0	20.00	18.0	0.04100	CLIPL-08
10.0	36.0	25.0	M8	44.0	23.00	19.0	0.06800	CLIPL-10
14.0	47.0	28.0	M10	55.0	25.50	26.0	0.13000	CLIPL-14
16.0	52.0	32.0	M12	65.0	28.00	26.0	0.21000	CLIPL-16
19.0	58.0	38.0	M12	78.0	32.0	30.0	0.28000	CLIPL-19
22.0	64.0	40.0	M12	86.0	43.50	32.0	0.40000	CLIPL-22
25.0	69.0	46.0	M14	94.0	43.50	32.0	0.44000	CLIPL-25